

FireStorm LED Tailgate Bar

INSTALLATION INSTRUCTIONS



STEP 1:

Clean the area between your tailgate and bumper thoroughly with warm soap and water. The adhesive on the mounting pads of your LED Tailgate Bar will only work once, so the installation area must be free of dust, dirt, and rust, and must be **COMPLETELY DRY** before installation.

STEP 2:

Measure the width of your tailgate and determine the midpoint of this distance by dividing the length by 2. Mark this midpoint, then measure on either side of this mark, and mark the two new points as well to determine the left to right orientation of the LED Tailgate Bar to insure that it is centered.

STEP 3:

The bar is oriented properly on the truck if the wires are coming out of the left side and LEDs are pointing straight out the back. Peel the backing off all of the adhesive pads on the back of the Tailgate Bar and press it very gently onto the vehicle between the marks from Step 2. Step back from the vehicle and make sure the bar is mounted straight. Detach and reapply the pads if necessary to correct the placement.

STEP 4:

Once the Tailgate Bar is attached, you will need to hard wire the Tailgate Bar into your truck. **DO NOT USE TRAILER HARNESS WIRING!** The following colors should be wired into the corresponding wires on your vehicle:

If your Truck has 1 bulb in the tail light that works for both brakes and turn signals, you will need to wire the FireStorm to the turn signals on the front of the truck, and the third (high-mount) brake light in order for the scanning function to work properly with both turn signals and brakes.

You can wire the FireStorm to use either Running Lights or Brake Lights with the Red LEDs. If you prefer the red LEDs to be on all the time with your running lights, splice it into the running light wire instead of the brake light wire.

BLACK – Connect to any Ground Wire or the – Terminal on your Battery.

RED – Connect to a Constant 12V+ Signal or the + Terminal on your Battery

GREEN – Splice in with the Positive Lead going to your Brake Light

YELLOW – Splice in with the Positive Lead going to your Left Turn Signal

BLUE – Splice in with the Positive Lead going to your Right Turn Signal

WHITE – Splice in with the Positive Lead going to your Reverse Lights

STEP 5:

REGISTER YOUR WARRANTY ONLINE OR BY SENDING THE ENCLOSED FORM!

Visit our website at www.plasmaglow.com

WARRANTY REGISTRATION
YOU CAN ALSO REGISTER YOU ONLINE AT
WWW.PLASMAGLOW.COM (CLICK THE WARRANTY LINK)

**Your warranty is not valid if your product is not registered within 30
days of purchase!**

Product: FireStorm Scanning LED Tailgate Bar

Name: _____

Address: _____

City: _____

State: _____ Zip Code: _____

Email: _____

Date of Purchase: _____

Store Name: _____

Price Paid (Excluding Tax): _____

Type of Vehicle: _____

Rate your satisfaction with this product (1-10) _____

Were the Instructions Easy to Follow: _____

Would you like us to mail you a catalog: _____

Why you purchased this product (Check All That Apply)

<input type="checkbox"/> Magazine Advertisement	<input type="checkbox"/> Store Recommendation
<input type="checkbox"/> Store Display	<input type="checkbox"/> PlasmaGlow Brand Name
<input type="checkbox"/> Catalog	<input type="checkbox"/> Warranty
<input type="checkbox"/> Friend's Recommendation	<input type="checkbox"/> Saw it at a Show

Please keep your receipt in a safe place

It is required to make a Warranty Claim

Please mail this completed form to:

PlasmaGlow
Product Registration
PO Box 2564
Gilbert, AZ 85299

OR REGISTER ONLINE AT WWW.PLASMAGLOW.COM